



-NOTES-

1. HOT DIP GALVANIZE PER SPEC ASTM A153-(LATEST REV).
2. STAMP ROD BEFORE GALV AS SHOWN IN TABLE WITH 1/4" FLAT FACE CHARACTERS.

CATALOG NUMBER	DESCRIPTION	"A"	STAMP
7557	THREADED TRIPLEYE ROD 3/4"	7'	C-3/4-7
7558	THREADED TRIPLEYE ROD 3/4"	8'	C-3/4-8
7559	THREADED TRIPLEYE ROD 3/4"	9'	C-3/4-9
-----	THREADED TRIPLEYE ROD 3/4"	6'	C-3/4-6

<b>CHANCE</b> TOLERANCE CHART <small>           1/16" = .0625" FRACTIONAL ANGLES 30°            1/32" = .03125" ANGLES 45°            1/64" = .015625" ANGLES 60°            1/128" = .0078125" ANGLES 75°            1/256" = .00390625" ANGLES 90°         </small>		<b>HUBBELL POWER SYSTEMS</b> <small>HUBBELL POWER SYSTEMS, INC.</small>	
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.			
TITLE <b>THREADED TRIPLEYE ROD 3/4"</b>		SIZE DWG NO. <b>C SA7556</b>	CAT / PART / ASSY NO. <b>SEE CHART</b>
DO NOT SCALE THIS DRAWING	DRN BY TNT	DATE 03/15/13	SHEET 1/1