



MAIN LINE RANGE - MAX. 2 1/2" O.D. BUS
 MAIN LINE RANGE - MIN 0.232 DIA.

ALUMINUM BODY
 SMOOTH JAWS
 BRONZE EYESCREW
 WITH ACME THREADS

CAT. NO. C600-1733

FAULT RATING FOR THIS GROUND CLAMP IS
 43,000 AMPS FOR 15 CYCLES AND 30,000 AMPS
 FOR 30 CYCLES. PER ASTM F855 SPEC.

| | | | | |
|-----------------------------------|------|----------|---|------------------------|
| LATEST EC NO: | REV. | DATE | CHANGED BY | RESP ENGINEER |
| 03288 | A | 10-18-01 | ELW | KING |
| DRN BY: DATE QUALLS 08-07-00 | | | DO NOT SCALE THIS DWG THIRD ANGLE PROJECTION ISO DUAL DIMENSIONS 1/8"=1INCH. MM=MILLIMETER | |
| TITLE: SUB-STATION BUS-CLAMP ASSY | | | | SIZE: C |
| | | | | DWG NO: SA600-1733 |

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF MURBELL. NO REPRODUCTION, DISTRIBUTION, OR PUBLICATION, IN ANY FORM OR BY ANY MEANS, IS PERMITTED WITHOUT THE WRITTEN CONSENT OF MURBELL. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS OF THE UNITED STATES OF AMERICA. © 2001 MURBELL/A. B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS