



ALUMINUM BODY  
SMOOTH JAWS  
BRONZE EYESCREW  
WITH FINE THREADS

MAIN LINE RANGE - MAX. 1.162 DIA.  
MAIN LINE RANGE - MIN. 0.162 DIA.

**CAT. NO. C600-1734**

FAULT RATING FOR THIS GROUND CLAMP IS  
36,000 AMPS FOR 15 CYCLES AND 25,000 AMPS  
FOR 30 CYCLES PER ASTM F855 SPEC.

LATEST EC NO:	REV.	DATE	CHANGED BY	RESP ENGINEER
EC02158	A	10-31-00	MARTIN	WEST

DRN BY: DATE QUALLS 08-07-00	TITLE: <b>GROUNDING CLAMP</b>	THIRD ANGLE PROJECTION 150 DUAL DIMENSIONS 1/8"=1" INCH. MM=MILLIMETER		SIZE <b>C</b>

			DWG NO: <b>SA600-1734</b>
--	--	--	------------------------------

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF MURBELL. NO REPRODUCTION, DISTRIBUTION, OR DISSEMINATION OF THIS DRAWING OR ITS CONTENTS IS PERMITTED WITHOUT THE WRITTEN CONSENT OF MURBELL. © 2001 MURBELL/A. B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS