



5/8-11UNC-2B  
TERMINAL THREADS

- ALUMINUM BODY
- SMOOTH JAWS
- BRONZE EYESCREW WITH FINE THREADS
- MAIN LINE RANGE - MAX 1.500 D1A.
- MAIN LINE RANGE - MIN 0.162 D1A

CAT. NO. C600-1743

FAULT RATING FOR THIS GROUND CLAMP IS 43,000 AMPS FOR 15 CYCLES AND 30,000 AMPS FOR 30 CYCLES PER ASTM F855 SPEC.

LATEST EC NO:		REV.	DATE	CHANGED BY	RESP ENGINEER
02160		-	-----	---	WEST
DRN BY: DATE TITLE:				DO NOT SCALE THIS DWG	THIRD ANGLE PROJECTION
QUALLS 18/89/153				ISO DUAL DIMENSIONS 1/8"=1INCH. MM=MILLIMETER	
CLAMP, GROUND					DIV NO: C
				DWG NO: SA600-1743	

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF MURBELL POWER SYSTEMS. NO REPRODUCTION, DISTRIBUTION, OR PUBLICATION, IN ANY FORM OR BY ANY MEANS, IS PERMITTED WITHOUT THE WRITTEN CONSENT OF MURBELL POWER SYSTEMS. © 2000 MURBELL/A. B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS