





ALUMINUM BODY
SMOOTH JAW
BRONZE EYESCREW
WITH ACME THREADS

(MAIN LINE RANGE)
1.00" - .162"

(JUMPER RANGE)
4/0 GRD CABLE - #2 GRD CABLE
WITH FERRULE

CATALOG NUMBER
C600-1754

FAULT RATING FOR THIS GROUND CLAMP
IS 28,000 AMPS FOR 15 CYCLES AND 20,000
AMPS FOR 30 CYCLES PER ASTM F855 SPEC.

LATEST EC NO:		REV.	DATE	CHANGED BY	RESP ENGINEER
02388		-	---	---	WEST
				DO NOT SCALE THIS DWG	THIRD ANGLE PROJECTION  ISO DUAL DIMENSIONS IN=INCH, MM=MILLIMETER
DRN BY:	DATE	TITLE:		SIZE	
QUALLS	2/14/01	GROUNDING CLAMP		B	
				 DWG NO: SA600-1754	

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL A.B. CHANCE COMPANY. NO PUBLICATION, DISTRIBUTION OR REPRODUCTION MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL A.B. CHANCE. © 2001 HUBBELL A.B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS