



ALUMINUM BODY
SERRATED JAWS
BRONZE 'T' HANDLE
WITH ACME THREADS

CAT. NO. CC600-1735

FAULT RATING FOR THIS CLAMP IS
25,000 AMPS FOR 15 CYCLES AND 25,000 AMPS
FOR 30 CYCLES PER ASTM F855 SPEC.

LATEST EC NO:	REV.	DATE	CHANGED BY	RESP ENGINEER
98071005	-	-----	---	KING
DRN BY: DATE TITLE: QUALLS 98-07-08 GROUNDING CLAMP				THIRD ANGLE PROJECTION ISO DUAL DIMENSIONS 1X=INCH. MM=MILLIMETER
				DWG NO: SA600-1798

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF MURBELL POWER SYSTEMS. NO REPRODUCTION, DISTRIBUTION, OR DISSEMINATION OF THIS DRAWING OR ITS CONTENTS IS PERMITTED WITHOUT THE WRITTEN CONSENT OF MURBELL POWER SYSTEMS. © 2000 MURBELL/A. B. CHANCE. UNPUBLISHED - ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS