

**Push-Button Switch
Product Features**

- Plastic case
- Nickel-plated brass nipple, knurled nut, hex nut
- Nipple 15/32" – 32 x 1/2" long

Compliances

- 
- 



6431



6426



6428



6427



6358

ORDERING INFORMATION - DIMENSIONS

MAINTAINED CONTACT SLIDE SWITCH – FOR LAMPS AND APPLIANCES				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6431	Slide, SPST, on-off Opening 9/16" x 7/8", Carded	5 amp, 250V AC 11 amp, 125V AC	5	

CONTACT PUSH-BUTTON SWITCHES – FOR BELLS AND BUZZERS				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6426	SPST Off-on, normally off, push on, Black, screw terminals, Carded	3 amp, 240V AC 6 amp, 120V AC	5	
6428	SPST Off-on, normally on, push off Red, screw terminals, Carded	1.5 amp, 277V AC 3 amp, 120V AC	5	

PUSH BUTTON SWITCH - FOR LAMPS AND APPLIANCES				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6358	Double Insulated, SPST, on-off 6" wire leads, Bulk Poly Bag	2 amp, 125V ACL 3 amp, 120V AC 1 amp, 250V AC	25	
6427	Push button SPST, on-off, 6" leads Carded	10 amp, 125V AC 8 amp, 125V AC 4 amp, 250V 1/3 HP, 125V AC	5	