

SPECIALTY TYPE SWITCHES

Product Features

- Impact-resistant thermoplastic body
- Silver cadmium oxide contacts
- Knurled nut, hex and strap all nickel-plated
- Keyed brass bushing
- #6-32 screw-type terminals
- Nickel-plated brass toggle
- Suitable for 12V DC use at rated amperage

Compliances

- 
- 



ORDERING INFORMATION - DIMENSIONS

EXTRA HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6415	DPST, on-off, Screw terminals, Carded	10 amp, 277V AC, 20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	
6419	DPDT, on-on, Screw terminals, Carded	10 amp, 277V AC, 20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	
6416	DPDT, on-off-on, Screw terminals, Carded	20 amp, 125V AC 1-1/2 HP, 125V/250V AC	5	

HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6410RAC	SPST, on-off Screw terminals Carded	12 amp, 250V AC 20 amp, 125V AC 1 HP, 120V/240V AC	5	
6413	SPDT, on-on Screw terminals Carded	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V/250V AC	5	
6411	SPDT, on-off-on Screw terminals	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V AC	5	
6420	SPST, on-off Screw terminals Carded	10 amp, 250V AC 20 amp, 125V AC 3/4 HP, 125V/250V AC	5	

EXTRA HEAVY-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6417	SPST, on-off Screw terminals Nonmetallic, Carded	20 amp, 125V/277V AC 1-1/2 HP, 125V AC 2 HP, 250V AC	5	
6418	DPDT, on-off-on Screw terminals Nonmetallic, Carded	20 amp, 125V/277V AC 2 HP, 250V AC 1-1/2 HP, 125V AC	5	

MEDIUM-DUTY BAT HANDLE TOGGLE SWITCH				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6414	SPST, on-off Screw terminals Carded	15 amp, 120V AC 10 amp, 240V AC	5	

