

Product Features

- Impact-resistant thermoplastic body
- Silver cadmium oxide contacts
- Knurled nut, hex and strap all nickel-plated
- Keyed brass bushing
- #6-32 screw-type terminals
- Nickel-plated brass toggle
- Suitable for 12V DC use at rated amperage

Toggle Boot Product Features

- Fits standard bat handle toggle switches
- Made of silicone rubber
- Fits nipples with 15/32" – 32 thread
- Packed two per card

Compliances

- 
- 



6412



6351



6409RAC



6441

ORDERING INFORMATION - DIMENSIONS

MEDIUM-DUTY BAT HANDLE TOGGLE SWITCH WITH WIRE LEADS

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6412	SPST, on-off, 6" leads Carded	4 amp, 250V 8 amp, 125V 10 amp, 125V AC 1/3 HP, 125V AC	5	

MEDIUM-DUTY BALL HANDLE TOGGLE SWITCH WITH WIRE LEADS

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6351	SPST, on-off, Ball handle Toggle for power tools & appliances, Nonmetallic with 6" wire leads, Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 3 amp, 125V ACL	25	

MEDIUM-DUTY BALL TOGGLE

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6409RAC	SPST, on-off Screw terminals, Carded	6 amp, 120V AC 3 amp, 240V AC	5	

TOGGLE BOOT

CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6441	Rubber cover & nut for toggle switch, Carded	-	5	